



# Viewing Station

model CVView



In a compact form factor, the perfect **viewing** complement to a CheckVideo solution.

**Reliable protection has never been this simple.**

The **CheckVideo Viewing Station (CVVIEW)** is a local viewer for on-site cameras. Live video is direct streamed from cameras and gateways with low latency. The CVVIEW is equally suited for guard desks, reception areas and command-center display walls and is compatible with standard HDMI displays. Matrix views from 4 to 36 live streams can be programmed for display. Any camera view can be displayed full-screen for detailed review.

The Viewing Station is a managed device and is remotely configured through the CheckVideo Video Management System (CVMS). Local configuration of cameras is also possible by using a user login which enables tours and custom views. CVVIEW also receives and applies software updates automatically and requires no on-site maintenance. It continues to function and display video from local cameras even during loss of Internet connectivity.

## SYSTEM

Fanless embedded computer with 4GB RAM capable of 1080p resolution

HDMI 1.4a Port

Integrated 10/100/1000 Ethernet Network connection

Embedded Linux OS with auto-updates

## ENVIRONMENT

### Operating temperature

0° C to +50° C

### Storage temperature

-10° C to +60° C

## VIDEO

### Inputs

IP video from up to 36 cameras. Supports CheckVideo cameras, Gateways and ExpressHD Recorders.

### Configuration

Remote Management and view configuration 2x2, 3x3, 4x4,5x5 or 6x6 matrix view

## MECHANICAL

### Dimensions

5" x 5" x 1.5" ( 127 mm x 127 mm x 38.1 mm )

VESA mount

### Power

12V DC back panel power connector

12V, 36W power supply included

