

5 MEGAPIXEL CLOUD MICRO DOME CAMERA

S1505



The **S1505** is a cloud managed IP camera with 5 megapixel resolution and built-in edge recording. The camera records video 24x7 to on-board storage eliminating the cost of an external NVR. With advanced video analytics for person and vehicle detection and superb low-light capability, it is the most compact all-in-one surveillance solution on the market. A single cable for data and power-over-Ethernet (PoE) makes it easy to install. The S1505 does not require any additional hardware or software on site for operation. Viewing, playback and camera configuration can be done through the CheckVideo Cloud VMS using just a web browser or mobile app. The camera supports cloud video backup as well as integration with VMS and alarm monitoring platforms for added peace-of-mind.

CAMERA



ADVANCED VIDEO ANALYTICS

Detection and classification of people, vehicles, and loitering. Advanced clutter rejection dramatically reduces false alarms by up to 85% compared to outdoor PIRs or cameras with motion detection.



LOW-LIGHT AND DAY/NIGHT SWITCHING

Exceptional low-light performance with a Sony Starvis™* sensor and multi-element glass lens. The camera automatically switches to night mode to allow ambient IR light for enhanced monitoring in dark scenes.



BUILT-IN DVR

Built-in 24/7 edge recording for 30 days at 1.5MP or 10 days at 5MP. Eliminating the need for a separate external NVR.

VIDEO MANAGEMENT



CLOUD FEDERATION

All cameras across multiple locations are federated into a single unified system that scales from one camera to thousands of cameras. This drastically reduces system cost and complexity.



WEB AND MOBILE VIEWING

Use a web browser to log into the cloud VMS and view live, playback recorded video or use our advanced search engine to find video in seconds. Our mobile apps also put this capability within easy reach.



INSTANT PUSH NOTIFICATIONS

When the camera detects an activity of interest, video notifications can instantly be sent by email, SMS or mobile push notification.







5 MEGAPIXEL CLOUD MICRO DOME CAMERA

0.1 lux

model S1505

CAMERA

Image Sensor 1/2.8" Progressive CMOS Minimum **Illumination Color**

Effective Pixels 2592x1944(5MP) Lens 2.8 mm focal length/F 1.6

VIDEO

Compression

Video H.264/H.265 Main Profile **Dual Streams** 2592 x 1944(5MP)/1440x1080(1.5MP)

VIDEO MANAGEMENT

Alarm Monitoring Bold Manitou, Micro Key MKMS, **Cloud VMS** Works with CheckVideo Cloud

> viewing, advanced search and cloud backup. No NVR needed on-site.

Integration SIMS II/III, Immix ®, SGS-stages VMS. Offers 100% web and mobile

ANALYTICS

Engine Auto-calibrating analytics with **Analytics** Person Detection, 10 to 60 feet

tracking and classification engine for Vehicle Detection, 30 to 75 feet people and vehicles.

Zone Violation Rejects clutter from environment and Loitering Person illumination changes. Stopped Vehicle

Video Alarm 10-second video clip generated upon

trigger of alarm; contains 2-4 seconds

of pre-alarm video

NETWORK

Wired 10/100Mbps Ethernet (RJ-45) **Protocols** IPv4/v6, TCP/IP, UDP, HTTP, HTTPS,

IGMP, DHCP, RTP/RTSP, HLS Security HTTPS, IP Filter, TLS 1.2

DVR

Web Player Resolutions Live streaming compatible with 5MP or 1.5MP

web browsers and mobile devices Recording Built-in 24/7 edge recording for 30

days at 1.5MP or 10 days at 5MP

GENERAL

Dimensions Ø 116 x 56 mm (Ø 4.56 x 2.20 in.) **Power Source** PoE 802.3af

Power 5W Operating -20°C ~ 55°C (-4°F ~ 131° F) Consumption Conditions

Humidity: 10% ~ 90%, no conden-

sation **Approvals** CE, FCC

Part Number 201696