

EXPRESSHD RECORDER

E1104-16





The CheckVideo ExpressHD Recorder (E1104-16) is an affordable, intelligent video surveillance system with built-in advanced video analytics and recording for up to 16 channels of HD video. Compatible with multiple video formats including NTSC, AHD, and TVI. The E1104-16 brings the most advanced video analytics that are 400% more accurate than motion detection. With 24x7 video recording built-in, the E1104-16 can record up to 30 days of HD video. It also includes HDMI output for a matrix display, plus automatic Cloud backup, all combined into a compact, low-power device. The E1104-16 provides enterprise features without breaking the budget.

The E1104-16 works with the CheckVideo Cloud VMS which enables remote configuration, viewing, and playback from a web browser. The CheckVideo Cloud VMS provides all ongoing video management with off-site Cloud backup, multi-location federation and a powerful video search engine.

GATEWAY



ADVANCED VIDEO ANALYTICS

Dramatically reduces false alarms by up to 85% vs. outdoor PIRs or cameras with builtin PIR detection.



DVR INCLUDED

Functions as primary DVR, for continuous recording and storage for up to 30 days.



SECURE OFFSITE STORAGE

Stores all alert video clips at an offsite location, ready for instant search and viewing.



FULL CLOUD VMS

Video backup, remote management, and health monitoring.

VIDEO MANAGEMENT



CHECKVIDEO CLOUD VMS

All CheckVideo solutions feature 100% Webbased video management functionality with no



MULTI-SITE FEDERATION

View cameras from multiple sites or recorders through a single interface, without ever having to log into the recorder.



AUTOMATED SYSTEM HEALTH MONITORING

The system automatically issues proactive alerts in case of camera tampering, poor video quality or loss of communication.



VIDEO SEARCH ENGINE

Find relevant video in seconds, saves hours of time compared to traditional DVR's.



CYBER-SECURITY INCLUDED

Hacker-proof and secured against network attacks.



EXPRESSHD RECORDER model E1104-16

APPLIANCE

Video Input 16 BNC connectors

Supports NTSC, AHD & TVI cameras over

coax cable up to 5MP

Video Output

Single HDMI output supports monitors up

to 1920x1080

VIDEO

H.264/H.265 Main/High-Profile Video Format

Video Encoding

Encodes all incoming video and streams to H.264/H.265 and restreams over RTSP

Video Recording

24x7 recording of video for up to 30 days, includes 12TB HDD

NETWORK

Bandwidth 2 Mbps upstream (min), not dedicated Connector

RJ-45 10/100/1000 Ethernet

Protocols

DHCP required, no static IP needed. TCP/IP, HTTP/HTTPS, NTP, RTSP

GENERAL

Dimensions 2" (h) x 12.3" (w) x 11.5" (d) Power Source/Power

Consumption

DC12V / 60W; 5.0A

Operating Conditions 0°C to 40°C (32°F to 104°F)

Weight

6.1 lbs.

Approvals

CE, FCC, NDAA Compliant

ALARM

Engine Calibration-free, auto-adapting analytics

Classification and Tracking Engine

Moving person

Moving vehicles

Detects moving objects (eliminates envi-

ronmental motion)

Video Alarm Clip

10-second video clip generated upon trigger of alarm, contains 2-4 seconds of

pre-alarm video

VIDEO MANAGEMENT

CheckVideo web-based Cloud VMS **VMS Software**

enables live, recorded and search functionality as well as configuration and management of an unlimited number of cameras across multiple sites

Health Monitoring

Poor video

Loss of communication Recording error

CLOUD BACKUP

Back up event video, with unlimited storage. Retention period available

from 5 days to 2 years.

ExpressHD

KPN 202072

ORDERING INFORMATION

ExpressHD Outdoor IR Mini-Dome

KPN 201579

BACK PANEL

Video Recording





