



Viewing Station

model V1101

In a compact form factor, the perfect **viewing** complement to a CheckVideo solution.

Reliable protection has never been this simple.

The **CheckVideo Viewing Station** (V1101) is a local viewer for on-site cameras. The V1101 is equally suited for guard desks, reception areas and command-center display walls and is compatible with standard HDMI displays. Matrix views from 4 to 36 live H.264/H.265 streams can be programmed for display. Any camera view can be displayed full-screen for detailed review. The layout can be modified and views can be saved for instant recall. Camera tours are also available.

The Viewing Station is a managed device and is remotely configured through the CheckVideo Video Management System (CVMS). V1101 also receives and applies software updates automatically and requires no on-site maintenance. It continues to function and display video from local cameras even during loss of Internet connectivity.

SYSTEM

Fanless embedded computer with media engine
Embedded Linux OS with auto-updates

Display

Port 1: HDMI 1.4, 1080p resolution
Port 2: HDMI 2.0, 4K resolution

Network

Integrated 10/100/1000 Ethernet Network connection

ENVIRONMENT

Operating temperature

0° C to 40° C

Storage temperature

-10° C to +60° C

ORDERING

Model: V1101 KPN: 202011

VIDEO

Inputs

IP video from up to 36 cameras. Supports CheckVideo cameras, Gateways and ExpressHD Recorders

Formats

H.264/H.265 encoded RTSP streams. Total decode capacity of 800 megapixels/sec.

Configuration

Remote Management and view configuration 2x2, 3x3, 4x4, 5x5 or 6x6 matrix view

MECHANICAL

Dimensions

6.1" x 5" x 1.75" (154.9 mm x 127 mm x 44.45 mm)/VESA mount

Power

12V DC back panel power connector/12V, 36W power supply included

BACK PANEL



www.checkvideo.com



info@checkvideo.com

© 2025 CheckVideo, LLC