



5 MEGAPIXEL AI DOME CAMERA

S2605



The **CheckVideo 5 Megapixel AI Camera** (S2605) is a complete video security solution that greatly simplifies installation while providing superior protection compared to traditional IP cameras and NVRs. With built-in 24x7 video recording, the S2605 eliminates the need for an external recorder. Featuring, patented compression technology, the 5MP Dome can record and transmit video using up to 70% less capacity resulting in reduced network and bandwidth costs.

With deep learning video analytics technology, the S2605 can differentiate people and vehicles from the normal motion generated by foliage and shadows, then instantly send an alert. The S2605 is part of the CheckVideo family of managed security solutions, and can be configured and viewed remotely by authorized users. Automated tamper detection, health checks and error recovery are included to ensure that security is never compromised. With Power-over-Ethernet connectivity, extreme low-light capability and built-in digital I/O, the S2605 combines simplicity and versatility in a compact package. The S2605 features one-click integration with the CheckVideo Cloud VMS, enabling a complete Cloud-based intelligent video security solution.

CAMERA



DEEP LEARNING AI VIDEO ANALYTICS

AI video analytics transform the camera into intelligent video sensors by accurately detecting people, vehicles, loitering and zone-of-interest violations. Includes Person and Vehicle tracking, Appearance Search, Counting and Object Classification.



BUILT-IN DVR

Records up to 30 days of HD video, eliminating the need for a separate external NVR or VMS.



SECURE VIDEO STREAMING

Allows simultaneous viewing of live video on multiple Web and mobile clients.



ULTRA LOW-LIGHT

Exceptional color images under challenging lighting conditions and long distances over 200 ft.

VIDEO MANAGEMENT



CHECKVIDEO CLOUD VMS

All CheckVideo solutions feature 100% Web-based video management functionality with no servers or software installation required.



VIDEO SEARCH ENGINE

Intelligent video search saves time by drilling down to the specific events of interest in seconds rather than hours.



AUTOMATED SYSTEM HEALTH MONITORING

The system issues proactive alerts in case of camera tampering, poor video quality or loss of communication.



CYBER-SECURITY INCLUDED

Hacker-proof and secure using 2048 bit certificates. Built-in firewall and encrypted communication for added security.

CAMERA

Image Sensor	1/2.8" 5 MP Progressive CMOS	Image Processing	Auto White Balance, Auto Exposure; 3D Noise Reduction; Wide Dynamic Range (WDR)
Light Sensitivity	Color: 0.15 lux; B/W with IR: 0 lux up to 130 ft. For longer range, use an external IR illuminator	Lens	2.8mm-13.5mm motorized varifocal lens with autofocus, 90° (wide) to 24° (zoom)

VIDEO

Video Compression	H.264/H.265 Main Profile	Resolutions	2592 x 1944(5MP)/1440x1080(1.5MP)
--------------------------	--------------------------	--------------------	-----------------------------------

VIDEO MANAGEMENT

Hosted Software	Compatible with NVRs and VMS servers. Works with CheckVideo CloudVMS which also offers web and mobile viewing, search engine and cloud backup.	Alarm Monitoring Integration	Bold Manitou, Micro Key MKMS, SIMS II/III, Immix®, SGS-stages
------------------------	--	-------------------------------------	---

ANALYTICS

Engine	Auto-calibrating analytics with tracking and classification engine for people and vehicles. AI Analytics for Object Classification, Counting, Appearance Search and Natural Language Processing.	Instant Notifications	Push Notifications to App, email or text message. Video clip contains pre and post alarm video.
Analytics	Person Detection, 10 to 260 feet Vehicle Detection, 30 to 320 feet Zone Violation Loitering Person Stopped Vehicle Detection distances vary with zoom	Tamper Alarm	Poor video Loss of communication
		Digital I/O (Access and Alarm Panel)	Digital Input: Normally Open. Close contact to trigger. Digital Output: Normally Open. Close on Detection. Max 60V 1A.

NETWORK

Wired	10/100/1000 Mbps Ethernet (RJ-45)	Protocols	IPv4/v6, TCP/IP, UDP, HTTP, HTTPS, IGMP, DHCP, RTP/RTSP, HLS
Security	HTTPS, IP Filter, TLS 1.2		

DVR

Resolutions	5MP or 1.5MP	Recording	Up to 30 days of continuous recording at 1.5MP or 14 days at 5MP
--------------------	--------------	------------------	--

GENERAL

Dimensions	Ø 140 x 108 mm (Ø 5.51 x 4.25 in.)	Power Source	PoE 802.3af, DC12V
Operating Conditions	-20°C ~ 50°C (4°F ~ 122°F) Humidity: 10% ~ 90%, no condensation. IP66 weatherproof rating	Power Consumption	8W
Connectors	RJ45, Audio Line Out, Terminal Block	Weight	2.02 lbs
		Approvals	CE, FCC, NDA Compliant

DETECTION RANGES

